

- Setup
- Wireless
- Services
- Security
- Access Restrictions
- NAT / QoS
- Administration
- Status
- Management
- Keep Alive
- Sysctl
- Commands
- WOL
- Factory Defaults
- Firmware Upgrade
- Backup

Router Management

Help [more...](#)

Router Password

Router Username

.....

Router Password

.....

Re-enter to confirm

.....

Auto-Refresh:
Adjusts the Web GUI automatic
refresh interval. 0 disables this feature
completely.

Web Access

Protocol

☐ HTTP ☐ HTTPS

Auto-Refresh (in seconds)

3

Enable Info Site

☐ Enable ☐ Disable

Remote Access

Web GUI Management

☐ Enable ☐ Disable

SSH Management

☐ Enable ☐ Disable

Telnet Management

☐ Enable ☐ Disable

Allow Any Remote IP

☐ Enable ☐ Disable

Boot Wait

Boot Wait

☐ Enable ☐ Disable

Cron

Cron

☐ Enable ☐ Disable

Additional Cron Jobs

802.1x

802.1x

☐ Enable ☐ Disable

Reset Button

Reset Button

☐ Enable ☐ Disable

Bootfail Handling

Reset after 5 Bootfails

☐ Enable ☐ Disable

Open Wifi after Bootfail

☐ Enable ☐ Disable

Keep IP after Bootfail

☐ Enable ☐ Disable

Routing

Routing

☐ Enable ☐ Disable

JFFS2 Support

Internal Flash Storage

☐ Enable ☐ Disable

Language Selection

Language

IP Filter Settings (adjust these for P2P)

TCP Congestion Control

Maximum Ports (Default: 4096, Range: 256 - 65536)

TCP Timeout (in seconds) (Default: 3600, Range: 1 - 86400)

UDP Timeout (in seconds) (Default: 120, Range: 1 - 86400)

Overclocking

Not Supported

Router GUI Style

Style

Use Dark Styles ☐ Enable ☐ Disable

DD-WRT Inspired themes

Theme

CIFS Automount

Common Internet File System ☐ Enable ☐ Disable

Show new Features

Display new Features ☐ Enable ☐ Disable

Save

Apply Settings

Cancel Changes

Reboot Router