

- Setup
- Wireless
- Services
- Security
- Access Restrictions
- NAT / QoS
- Administration
- Status
- Management
- Keep Alive
- Sysctl
- Commands
- WOL
- Factory Defaults
- Firmware Upgrade
- Backup

Router Management

Help [more...](#)

Router Password

Router Username

Router Password

Re-enter to confirm

Auto-Refresh:

Adjusts the Web GUI automatic refresh interval. 0 disables this feature completely.

Web Access

Protocol  HTTP  HTTPS

Auto-Refresh (in seconds)

Enable Info Site  Enable  Disable

Remote Access

Web GUI Management  Enable  Disable

SSH Management  Enable  Disable

Telnet Management  Enable  Disable

Allow Any Remote IP  Enable  Disable

Boot Wait

Boot Wait  Enable  Disable

Cron

Cron  Enable  Disable

Additional Cron Jobs

802.1x

802.1x  Enable  Disable

Reset Button

Reset Button  Enable  Disable

Bootfail Handling

Reset after 5 Bootfails  Enable  Disable

Open Wifi after Bootfail  Enable  Disable

Keep IP after Bootfail  Enable  Disable

Routing

Routing  Enable  Disable

JFFS2 Support

Internal Flash Storage  Enable  Disable

Language Selection

Language

IP Filter Settings (adjust these for P2P)

TCP Congestion Control  (Default: 4096, Range: 256 - 65536)  
Maximum Ports   
TCP Timeout (in seconds)  (Default: 3600, Range: 1 - 86400)  
UDP Timeout (in seconds)  (Default: 120, Range: 1 - 86400)

Overclocking

Not Supported

Router GUI Style

Style    
Use Dark Styles  Enable  Disable

DD-WRT Inspired themes

Theme

CIFS Automount

Common Internet File System  Enable  Disable

Show new Features

Display new Features  Enable  Disable