

- Setup
- Wireless
- Services
- Security
- Access Restrictions
- NAT / QoS
- Administration
- Status
- Management
- Keep Alive
- Sysctl
- Commands
- WOL
- Factory Defaults
- Firmware Upgrade
- Backup

Router Management

Help

[more...](#)

Router Password

Router Username

Router Password

Re-enter to confirm

Auto-Refresh:

Adjusts the Web GUI automatic refresh interval. 0 disables this feature completely.

Web Access

Protocol HTTP HTTPS

Auto-Refresh (in seconds)

Enable Info Site Enable Disable

Remote Access

Web GUI Management Enable Disable

SSH Management Enable Disable

Telnet Management Enable Disable

Allow Any Remote IP Enable Disable

Boot Wait

Boot Wait Enable Disable

Cron

Cron Enable Disable

Additional Cron Jobs

802.1x

802.1x Enable Disable

Reset Button

Reset Button Enable Disable

Bootfail Handling

Reset after 5 Bootfails Enable Disable

Open Wifi after Bootfail Enable Disable

Keep IP after Bootfail Enable Disable

Routing

Routing Enable Disable

JFFS2 Support

Internal Flash Storage Enable Disable

Language Selection

Language

IP Filter Settings (adjust these for P2P)

TCP Congestion Control
Maximum Ports (Default: 4096, Range: 256 - 65536)
TCP Timeout (in seconds) (Default: 3600, Range: 1 - 86400)
UDP Timeout (in seconds) (Default: 120, Range: 1 - 86400)

Overclocking

Not Supported

Router GUI Style

Style
Use Dark Styles Enable Disable

DD-WRT Inspired themes

Theme

CIFS Automount

Common Internet File System Enable Disable

Show new Features

Display new Features Enable Disable