

Setup | **Wireless** | Services | Security | Access Restrictions | NAT / QoS | Administration | Status

Basic Settings | Radius | **Wireless Security** | MAC Filter | Advanced Settings | WDS

Country Settings

Help [more...](#)

Regulatory Domain

Regulatory Domain: UNITED_STATES

Regulatory Mode: Off

TPC Mitigation Factor: 0 (Off)

Attention: It is recommended that you press *Apply Settings* after you change a value in order to update the fields with the corresponding parameters.

Wireless Physical Interface w10 [2.4 GHz]

Physical Interface w10 - SSID [dd-wrt] HWAddr [14:DD:A9:F2:6C:82]

Wireless Mode: AP

Wireless Network Mode: Mixed

Wireless Network Name (SSID): dd-wrt

Wireless Channel: 9 - 2.452 GHz

Channel Width: 20 MHz

Wireless SSID Broadcast: Enable Disable

Sensitivity Range (ACK Timing): 500 (Default: 500 meters)

Multicast To Unicast: Enable Disable

Network Configuration: Unbridged Bridged

Copy Paste

Virtual Interfaces

Virtual Interfaces w10.1 SSID [dd-wrt_vap] HWAddr [16:DD:A9:F2:6C:83]

Wireless Network Name (SSID): dd-wrt_vap

Wireless SSID Broadcast: Enable Disable

AP Isolation: Enable Disable

Network Configuration: Unbridged Bridged

Multicast forwarding: Enable Disable

Net Isolation: Enable Disable

Forced DNS Redirection: Enable Disable

IP Address: 192 . 168 . 10 . 1

Subnet Mask: 255 . 255 . 255 . 0

Remove Copy Paste

Add Virtual AP

Save Apply Settings Cancel Changes