

- Setup
- Wireless
- Services
- Security
- Access Restrictions
- NAT / QoS
- Administration**
- Status
- Management
- Keep Alive
- Sysctl
- Commands
- WOL
- Factory Defaults
- Firmware Upgrade
- Backup

Router Management

Login Credentials

Username

Password

Re-enter to Confirm

Web Access

Protocol  HTTP  HTTPS

Auto Refresh  seconds

Enable Info Site  Enable  Disable

Info Site Password Protection  Enabled

Info Site MAC Masking  Enable  Disable

Remote Access

Web UI Management  Enable  Disable

SSH Management  Enable  Disable

Telnet Management  Enable  Disable

Allow any Remote IP  Enable  Disable

Boot Time Recovery

Boot Wait  Enable  Disable

Cron

Enable Cron  Enable  Disable

Additional Jobs

Reset Button

Enable Button  Enable  Disable

Bootfail Handling

Reset after 5 Bootfails  Enable  Disable

Open WiFi after Bootfail  Enable  Disable

Keep IP after Bootfail  Enable  Disable

JFFS2 Support

Enable Flash Storage  Enable  Disable

Language Selection

Language

Network Stack Tuning

TCP Congestion Control

Maximum Connections  (Default: 4096, Range: 256 - 65535)

Help

more...

Auto Refresh:

Adjust the Web interface refresh interval. Enter a value of 0 to disable this feature. The default value is 3 seconds.

JFFS2 Support:

When you first **Enable Flash Storage**, it is necessary to enable **Wipe Flash Storage** in order to prepare the flash file system for usage.

Network Stack Tuning:

Advanced users can use the sysctl tab to further tune the network stack beyond the limited set of options available here. Any settings available on sysctl should be handled with caution, ensure you have a current backup before proceeding in case changes have undesired results.

TCP Timeout	<input type="text" value="3600"/> seconds	(Default: 3600, Range: 1 - 86400)
UDP Timeout	<input type="text" value="120"/> seconds	(Default: 120, Range: 1 - 86400)

**Overclocking**

Not Supported

**Web UI Styles**

Select a Style

Enable Dark Styles  Enable  Disable

Enable Sticky Footer  Enable  Disable

**DD-WRT Inspired Themes**

Select a Theme

**Common Internet File System (CIFS)**

CIFS Automount  Enable  Disable