

- Setup
- Wireless
- Services
- Security
- Access Restrictions
- NAT / QoS
- Administration**
- Status
- Management
- Keep Alive
- Sysctl
- Commands
- WOL
- Factory Defaults
- Firmware Upgrade
- Backup

Router Management

Help [more...](#)

**Login Credentials**

Username

Password

Re-enter to Confirm

**Auto Refresh:**

Adjust the Web interface refresh interval. Enter a value of 0 to disable this feature. The default value is 3 seconds.

**JFFS2 Support:**

When you first **Enable Flash Storage**, it is necessary to enable **Wipe Flash Storage** in order to prepare the flash file system for usage.

**Web Access**

Protocol  HTTP  HTTPS

Auto Refresh  seconds

Enable Info Site  Enable  Disable

Info Site Password Protection  Enabled

Info Site MAC Masking  Enable  Disable

**Network Stack Tuning:**

Advanced users can use the sysctl tab to further tune the network stack beyond the limited set of options available here. Any settings available on sysctl should be handled with caution, ensure you have a current backup before proceeding in case changes have undesired results.

**Remote Access**

Web UI Management  Enable  Disable

SSH Management  Enable  Disable

Telnet Management  Enable  Disable

Allow any Remote IP  Enable  Disable

**Boot Time Recovery**

Boot Wait  Enable  Disable

**Cron**

Enable Cron  Enable  Disable

Additional Jobs

**Reset Button**

Enable Button  Enable  Disable

**Bootfail Handling**

Reset after 5 Bootfails  Enable  Disable

Open WiFi after Bootfail  Enable  Disable

Keep IP after Bootfail  Enable  Disable

**JFFS2 Support**

Enable Flash Storage  Enable  Disable

**Language Selection**

Language

**Network Stack Tuning**

TCP Congestion Control

Maximum Connections  (Default: 32768, Range: 256 - 65535)

|             |                                   |         |                                   |
|-------------|-----------------------------------|---------|-----------------------------------|
| TCP Timeout | <input type="text" value="3600"/> | seconds | (Default: 3600, Range: 1 - 86400) |
| UDP Timeout | <input type="text" value="120"/>  | seconds | (Default: 120, Range: 1 - 86400)  |

**Overclocking**

Not Supported

**Web UI Styles**

Select a Style

Enable Dark Styles  Enable  Disable

Enable Sticky Footer  Enable  Disable

**DD-WRT Inspired Themes**

Select a Theme

**Common Internet File System (CIFS)**

CIFS Automount  Enable  Disable

**Display New Features**

Show Features  Enable  Disable